

ROUND SLING

SPECIFICATION FOR 2 TONNE - GREEN

**AS
4497.1**



Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank. Conforms to Australian Standard AS 4497.1. Black colour available upon request.

Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.



WORKING LOAD LIMITS CHART (KG) - (WLLs)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
GREEN	2000	1600	4000	3400	2800	2000	2,760	2,760

NSW Head Office

43 Frank Street
 Wetherill Park, NSW 2164
 02 9757 2277

WA Office

42 Mulgool Road
 Malaga, WA 6090
 08 9248 6674

QLD Office

7 Durbell Street
 Acacia Ridge, QLD 4110
 07 3272 0777

VIC Office

47 Technology Drive
 Sunshine West, VIC 3020
 03 9314 5525