

# ROUND SLING

## SPECIFICATION FOR 3 TONNE - YELLOW

**AS  
4497.1**



### Round Sling - Polyester

Every Austlift sling is fabricated using 100% high tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank. Conforms to Australian Standard AS 4497.1. Black colour available upon request.

### Application

- Building construction sites
- Ship building yards
- Factory production workshops
- Mine production sites
- Engineering workshops

### Features

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under protective sleeve, to prevent damage to it.



WLL 3000KG		
WLL 3000KG YELLOW		
CODE	LENGTH(M)	Wt. (kg)
900305	0.5	0.38
900310	1.0	0.62
900315	1.5	0.94
900320	2.0	1.22
900325	2.5	1.57
900330	3.0	1.83
900335	3.5	2.21
900340	4.0	2.48
900345	4.5	2.85
900350	5.0	3.02
900355	5.5	3.49
900360	6.0	3.71
900380	8.0	4.92
900391	10.0	6.2

### WORKING LOAD LIMITS CHART (KG) - (WLLs)

ROUND SLING								
	VERTICAL	CHOKE	BASKET	60°	90°	120°	SINGLE WRAP Max 45°	DOUBLE WRAP Max 45°
YELLOW	3000	2400	6000	5100	4200	3000	4,140	4,140